

SUPER CARRY



SUPER CARRY



SPECIFICATIONS

Number of doors	2
Steering	RHD
Drive system	2WD
Fuel type	Petrol
Engine	1.2L
Body type	Truck
Transmission	5MT

DIMENSIONS

Overall length		mm	3,800
Overall width		mm	1,562
Overall height		mm	1,883
Wheelbase		mm	2,110
Front overhang		mm	925
Rear overhang		mm	765
Tread	Front	mm	1,345
	Rear	mm	1,330
Minimum turning radius		m	4.3
Cargo bed length		mm	2,183
Cargo bed width		mm	1,488
Cargo bed height		mm	300
Minimum ground clearance		mm	175

CAPACITIES

Seating capacity	3	
Fuel tank capacity	litres	30 Ltr

WEIGHTS

Maximum payload	kg	750
Gross vehicle weight	kg	1,600

ENGINE

Type	G12B	
Number of cylinders	4	
Number of valves	16	
Piston displacement	cm³	1,196
Bore x stroke	mm	71x75.5
Compression ratio	10.0	
Maximum output	kW/rpm	54/6,000
Maximum torque	N•m/rpm	101/3,000
Fuel distribution	Multipoint injection	

TRANSMISSION

Type		
Gear ratio	1st	4.425
	2nd	2.304
	3rd	1.674
	4th	1.264
	5th	1.000
	Reverse	5.151
Final gear ratio		3.727

CHASSIS

Steering		Manual
Brakes	Front	Ventilated disc (13inch)
	Rear	Drum, leading & trailing
Suspension	Front	MacPherson strut with coil spring
	Rear	Rigid axle with leaf spring
Tyres		155R13LT8PR

These specifications are subject to change without prior notice.
Specifications may vary for individual markets.

Warranty for 3 years / 100,000 km

CFAO MOTORS UGANDA ADDRESS

KAMPALA BRANCH

- Plot 1, First Street, Industrial Area.
- 0312301600 / 0800211033
- cfaomotors.ug@cfao.com
- _Suzuki_Uganda
- suzukiuganda
- suzukiuganda
- www.suzuki.ug

NAMANVE BRANCH: Plot 668, Industrial & Business Park, Namanve

GULU BRANCH: Plot 18, Goma-Kitgum Road

MBALE BRANCH: Plot 28 Mwanyi Road

